Via Friuli Venezia Giulia, 15 30030 Pianiga (VE) Italy Tel. +39 041 5101622 Fax. +39 041 5131351

P. Iva 03470750278 Reg.Imp. Ve 03470750278 Cap. Soc. Euro 90.000,00 REA Padova n ° 311219

www.prosystemitalia.com info@prosystemitalia.com



FIRE PROTECTION EXPANSION JOINTS GROOVED "U" FM - prosystemitalia.com

FIRE PROTECTION EXPANSION JOINTS GROOVED "U" FM



Application

Fire protection expansion joint \pm 100mm FM approved.

Assemblies consist of parallel corrugated metal hoses with carbon steel braiding, connections, turns and elbows. The fl exible metal hose provides high movement capacity in all direction of assembly and the braiding increases the pressure resistance accordingly.

Technical data

Movements: ±100 mm


Bellow material: Stainless steel AISI316L Braiding material: Stainless steel AISI304

Nominal diameter: 2" - 8"

Operating pressure: 175, 250 psi Operating temperature: -80°C/+600°C

Connection types: grooved

Connection material: Carbon steel St.37.2 Elbow and turn material: Carbon steel St.37.2



SIZE	Movement	Ødi	s	В	L	b
[_				
[]				Ĩ.	7	
	-				*	
DN50-2"	+/- 4"	60,3	2,9	466	635	55
DN65-21/2"	+/- 4"	76,1	2,9	490	715	55
DN80-3"	+/- 4"	88,9	3,2	560	762	55
DN100-4"	+/- 4"	114,3	3,6	718	890	55
DN125-5"	+/- 4"	139,7	4	880	1020	60
DN150-6"	+/- 4"	165,1	4,5	1040	1170	60
DN200-8"	+/- 4"	219,1	6	1350	1475	65

Approvals

FM Approved



Tipo	Kg	Pezzi per confezione	Codice Articolo
	25	1	MUS100
	0	1	MUS050
	0	1	MUS065
	0	1	MUS080
	0	1	MUS125
	33	1	MUS150
	0	1	MUS200
219,1 mm 8''	0	1	MUS250