

PRATIK BI AND BIPT INOX A2 - prosystemitalia.com

PRATIK BI AND BIPT INOX A2



Use

BI INOX clamp without threaded rod and plug, code from 392201 to 392212.

Including threaded rod and nylon plug. Suitable for wall, ceiling or floor fixing, code from 392214 to 392225.

Warning: do not use these collars in the presence of thermal expansion.

Technical data

Material: A2 stainless steel (AISI 304).

Attack: Electrowelded hex nut.

Type	Pipe diam. ext. [mm]	Pipe clamp sect. [mm]	Perm. axial load [kN]	Perm. tension load [kN]
M8 x 1/2"	20 - 24	20 x 2	1	1,6
M8 x 3/4"	25 - 30	20 x 2	1	1,6
M8 x 1"	32 - 36	20 x 2	1	1,6
M8 x 1" 1/4	39 - 44	20 x 2	1	1,6
M8 x 1" 1/2	46 - 50	20 x 2	1	1,6
M8 x 2"	58 - 64	20 x 2	1	1,6
M10 x 2" 1/2	74 - 80	29 x 2	1,6	4
M10 x 3"	84 - 89	29 x 2	1,6	4
M10 x 4"	112 - 118	29 x 2	1,6	4
M10 x 5"	135 - 142	29 x 2	1,6	4
M10 x 6"	165 - 171	29 x 2	1,6	4

Tipo	Kg	Pezzi per confezione	Codice Articolo
	0.09	100	392201
1/2"	0.09	100	392200

Tipo	Kg	Pezzi per confezione	Codice Articolo
	0.1	100	392202
	0.1	100	392203
	0.11	100	392204
	0.12	100	392205
	0.26	100	392206
2"	0.26	100	392207M8
	0.27	100	392207
	0.28	100	392208
3'	0.28	100	392208M8
	0.34	100	392210
4"	0.34	100	392209
	0.37	100	392211
	0.41	100	392212
6"	0.41	100	392213
	0.46	100	392225