

Prosystem Italia Srl

Via Friuli Venezia Giulia, 15
30030 Pianiga (VE) Italy
Tel. +39 041 5101622
Fax. +39 041 5131351

P. Iva 03470750278
Reg.Imp. Ve 03470750278
Cap. Soc. Euro 90.000,00
REA Padova n° 311219

www.prosystemitalia.com
info@prosystemitalia.com



GATE VALVE OS&Y PN16 UL/FM - prosystemitalia.com

GATE VALVE OS&Y PN16 UL/FM



Application

Rubberized wedge gate valve with external screw OS&Y model.
Suitable for both vertical and horizontal installations

Technical data

Connections: flanged EN1092-2 PN16
ANSI / AWWA C550 malleable cast iron body
Rubberized wedge in EPDM
Stem in stainless steel
EPDM O-Ring
EPDM gasket
Maleable cast iron handwheel
Body coated in RAL3000 red epoxy paint
Max working pressure: 20 bar up to 10 "; 12": 17 bar
Max working temperature: 70 ° C

Certificates

UL / FM approved

Tipo	Kg	Pezzi per confezione	Codice Articolo
DN 65	20	1	850600
DN 80	24	1	850601
DN 100	43	1	850602
DN 150	70	1	850603
DN 200	112	1	850604
DN 250	159	1	850605
DN 300	220	1	850606
Switch	5	1	850625