


GROOVED BUTTERFLY VALVE W.HANDWHEEL - prosystemitalia.com

GROOVED BUTTERFLY VALVE W.HANDWHEEL



Application

Full bore ball valve for water and fluids with connections for grooved pipe. Manual operation with wheel. Ready to attack actuator ISO 5211 and DIN 3337.

Technical data

Connection: grooved

Operation: 90 ° rotation of the control member.

Nominal pressure: PN 25.

Working temperature: from - 20°C to + 160°C.

Flow direction: in both directions.

Pressure drop: see Kv in the table.

NB	Ø [inches]	A [mm]	B [mm]	ØC [mm]	ØD [mm]
50	2"	177	84	90	60,3
65	2" 1/2	197	97	90	76,1
80	3"	207	97	90	88,9
100	4"	255	116	90	114,3
125	5"	261	148	90	139,7
150	6"	328	148	90	168,3
200	8"	381	133	125	219,1

Material:

- Body: brass CW617N
- Ball: brass CW614N
- Seat ring, packing: P.T.F.E.
- O-ring: NBR 70Sh.
- Washer, ratchet, screw, reatainer, nut: steel.

Warnings

We recommend the use of the valve in fully open or closed, not in mid. Operate at least twice a year.

Approval

EN 593.

Tipo	Kg	Pezzi per confezione	Codice Articolo
273,0 mm 10"	32	1	VSV-273
323,9 mm 12"	37	1	VSV-324
219,1 mm 8"	23	1	VSV-219